

Lean Dolly type I

The Lean Dolly Type I is equipped with 2 fixed and 2 swivel wheels.

It is designed to carry plastic crates and trays used in the automotive industry. It can easily be integrated into your automated system and used with or without a drawbar.

For optimised external transport and warehousing the Lean dolly can be used together with the Lean adaptor pallet for the warehousing and distribution of components.

The Lean dolly, also known as Bodenroller on our biggest market Germany, is also available in ISO and US dimensions: 24" x 15" and 24" x 22.5".



Key benefits

- ✓ Improve work flow
- ✓ Reduce handling costs
- ✓ Enable reduction of stock level
- ✓ Reduce need for floor space
- ✓ Improve ergonomics
- ✓ Fast and safe truck loading
- ✓ Optimised vehicle fill

Technical specifications

External dimensions	600 x 400 x 157 mm
Tare weight	6,5 kg
Wheel size	100 mm
Wheel type	2 fixed, 2 swivel
Wheel material	CPD, rubber or PU
Working capacity	250 kg
Surface treatment	Zinc electroplated
Lean Adaptor Pallet compatibility	Next Generation (DOS1696 & DOS1725), Type III (DOS1405)
Safe stacking up to 15 pieces	1950 mm

Images



Accessories & Extra

Total brake on 1 or 2 swivel wheels	RFID & Tracking ready
Ergonomic handle	Strapping device
Oil dripping pan	Also available in ISO and US dimensions: 24" x 15" 24" x 22.5"
Compound wheel	Rubber wheel
ESD hard plastic wheel and non-marking ESD hard plastic wheel	Polyurethane wheel or polyurethane ESD wheel

Designed for following uses and industries



Videos

[www.youtu.be/cZA7sF722Uc](https://www.youtube.be/cZA7sF722Uc)

[k-hartwall.com](https://www.k-hartwall.com)

youtube.com/user/KHartwall

linkedin.com/company/k.-hartwall-oy-ab

instagram.com/khartwall