Lean Modular Dolly

The Lean Modular Dolly is a 600×400 mm Dolly which can be customised with different add-on features depending on your product flow and the packages to be carried. You can add for example a drawbar, side or corner supports or even modify the position of the wheels.

It is designed to carry plastic crates and trays used in the automotive industry. Available in 1/4 pallet size, it can easily be integrated into your automated system, tugger trains and used with or without a drawbar.

For optimised external transport and warehousing the Lean Modular Dolly, also known as Bodenroller on our biggest market Germany, can be used together with the Lean adaptor pallet for the warehousing and distribution of components.

Also availabe in US dimensions: 24" x 15" and 24" x 22.5"



Key benefits

- Improve work flow
- Reduce handling costs
- Enable reduction of stock level
- Reduce need for floor space
- Improve ergonomics
- Fast and safe truck loading
- Optimised vehicle fill

Technical specifications

Wheel size

Working capacity

External dimensions 600 x 400 x 157 mm

Tare weight 6,3 kg

Wheel type 2 fixed, 2 swivel

Wheel material CPD, rubber or PU

Surface treatment Zinc electroplated

Lean Adaptor Pallet compatibility Next Generation (DOS1696 & Samp; DOS1725),

Type III (D0S1405)

Safe stacking up to 15 pieces

1950 mm

100 mm

250 kg

Images





Designed for following uses and industries









Accessories & Extra

Total brake on 1 or 2 swivel wheels RFID & Tracking ready

Also availabe in US dimensions 24" x 15" 24" x 22.5"

Compound wheel

Rubber wheel ESD hard plastic wheel and

non-marking ESD hard plastic

wheel

Polyurethane wheel or polyurethane ESD wheel

Videos

www.youtu.be/cZA7sF722Uc

k-hartwall.com

youtube.com/user/KHartwall

in linkedin.com/company/k.-hartwall-oy-ab

(instagram.com/khartwall