

SmartCube®

The SmartCube can boost space efficiency by lowering drastically the amount of air transported.

Its solid construction keeps the transported goods safe & sound and eliminates the need for shrink wrap – a fact that lowers costs and enhances product visibility.

Most stillages have only half drop-down gates but the SmartCube has also opening gates on one side, which enables loading from both sides.

The SmartCube is extremely durable and requires very little repair or maintenance.

Our different SmartCube models (Standard, Jumbo, Standing items) are all compatible with each other.

Please note that the SmartCube is also available in ISO Size (1000 x 1200 mm footprint).




Key benefits

- ✓ No loose parts
- ✓ No shrink wrap
- ✓ Access from both sides for easy loading
- ✓ Takes seconds to put in operational mode
- ✓ Fully stackable when folded or assembled
- ✓ Very low total cost of ownership

Technical specifications

External dimensions	1224 x 817 x 1210 mm
Internal dimensions	1102 x 695 x 985 mm
Unit tare weight	72 kg
Safe working load	1000 kg
Loaded units / 13,5m trailer	64
Stacked units / 13,5m trailer	192
Stacking height - empty	397 mm
Max stacking (empty)	12 high
Max stacking (loaded)	4 high (3 on 1)
Finish	Zinc electroplate and lacquer

Images



Accessories & Extra

Additional half-drop down opening Without skids on the short side

Compatible with SmartCube Jumbo and SmartCube Standing items

Videos

www.youtube.be/_JSZ3EQXIMg

k-hartwall.com

linkedin.com/company/k-hartwall-oy-ab

youtube.com/user/KHartwall

instagram.com/khartwall

Designed for following uses and industries

